

Bugs & Wish list

`session_protected` feature is broken if HTTPS termination happens outside of PHP's reach | Tiki Wiki CMS Groupware :: Development
`session_protected` feature is broken if HTTPS termination happens outside of PHP's reach

Status

● Open

Subject

`session_protected` feature is broken if HTTPS termination happens outside of PHP's reach

Version

18.x

Category

- Bug

Resolution status

New

Submitted by

Jan Chren

Lastmod by

Jan Chren

Rating

★★★★★ (0) ?

Description

In `tiki-setup_base.php` file there is a broken piece of code that looks like this:



```
<?php $noSSLActive = ! isset($_SERVER['HTTPS']) || (isset($_SERVER['HTTPS']) &&
$_SERVER['HTTPS'] == 'off'); if (isset($prefs['session_protected']) &&
$prefs['session_protected'] == 'y' && $noSSLActive && php_sapi_name() != 'cli') {
header("Location: https://{$_SERVER['HTTP_HOST']}{$_SERVER['REQUEST_URI']}"); exit; }
```

which results in infinite loops if 'session_protected' is set to 'y' and `HTTPS` variable is not set. Also this piece of code doesn't handle different base urls, ports, ...

Importance

3

Easy to solve?

3

Priority

9

Demonstrate Bug (Tiki 19+)

Please demonstrate your bug on show2.tiki.org

Version: trunk ▼

Demonstrate Bug (older Tiki versions)

Ticket ID

6583

Created

Wednesday 28 February, 2018 21:01:57 GMT-0000
by Jan Chren

LastModif

Wednesday 28 February, 2018 21:01:57 GMT-0000

Comments

Attachments

filename	created	hits	comment	version	filetype
----------	---------	------	---------	---------	----------

No attachments for this item

The original document is available at

https://dev.tiki.org/item6583--session_protected-feature-is-broken-if-HTTPS-termination-happens-outside-of-PHP-s-reach